



### Main

Range	Linergy
Product name	Linergy FM
IP degree of protection	IP20
Product or component type	Device feeder
Product compatibility	Spacial enclosures

### Complementary

Mounting support	Plain backplate DIN rail Slotted backplate
Mounting mode	By screws Clip-on
Installed device	Modular device
Poles description	3P + N
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	80 A
[Ipk] rated peak withstand current	12 kA
I <sup>2</sup> t on activation	2400000 A <sup>2</sup> .s
Connections - terminals	Supply : tunnel type terminal 25 mm <sup>2</sup> (flexible) Supply : tunnel type terminal 35 mm <sup>2</sup> (rigid) Distribution : quick-connect terminal strips (phase) , 18 x 4...6 mm <sup>2</sup> Distribution : quick-connect terminal strips (neutral) , 18 x 4...6 mm <sup>2</sup>
Total number of 18 mm modules	24
Product weight	0.902 kg
Colour	Anthracite grey RAL 7016

## Environment

Standards	IEC 61439-1 inside Prisma IEC 61439-2 inside Prisma IEC 60947-7-1
Product certifications	ASEFA

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------